

Appl. No. 10/799,913  
Amdt. Dated October 26, 2005  
Reply to Office Action of October 19, 2005

Docket No. CM06187H  
Customer No. 22917

**Listing of Claims:**

1. (currently amended) In a wireless communication system with an air interface comprising a plurality of bursts, a method comprising the step of defining a plurality of bursts, wherein each burst comprises a field embedded within the burst; and wherein the field is one taken from the group of a synchronization field and a signaling field; and wherein, when the field is a synchronization field, defining a position of at least one subsequent burst comprising the signaling field, and defining a position of at least one subsequent burst comprising the synchronization field; wherein, when the field is a signaling field, defining an indicator in a framing portion of the signaling field to identify that payload in the burst is taken from the group of a) begins a new packet, b) completes a packet, and ~~b)c)~~ does not begin or complete a packet; ~~and wherein at least one burst comprising the signaling field carries link control signaling and framing information for the link control signaling.~~
2. (original) The method of claim 1 wherein the signaling field carries non-voice information.
3. (original) The method of claim 1 wherein each burst comprising the signaling field comprises one of a link control signaling, and an encryption parameter.
4. (currently amended) The method of claim 1 wherein at least one burst comprising the signaling field carries link control signaling ~~and framing information for the link control signaling.~~
5. (previously presented) The method of claim 1 wherein an encryption parameter is carried in one of the bursts comprising the signaling field, and wherein a receiving device of the plurality of bursts knows a location of the burst carrying the encryption parameter *a priori*.

Appl. No. 10/799,913  
Amdt. Dated October 26, 2005  
Reply to Office Action of October 19, 2005

Docket No. CM06187H  
Customer No. 22917

6. (withdrawn) The method of claim 4 wherein, when the field is a signaling field, defining an indicator to identify that payload in a burst begins a new packet.
7. (withdrawn) The method of claim 4 wherein, when the field is a signaling field, defining an indicator to identify that payload in a burst completes a packet.
8. (withdrawn) The method of claim 4 wherein, when the field is a signaling field, defining an indicator to identify that payload in a burst does not begin or complete a packet.
9. (previously presented) The method of claim 1 wherein the link control signaling is formed into a matrix, having rows and columns, prior to forward error correction encoding, wherein the rows of the matrix are encoded with a block code, and wherein the columns of the matrix are encoded with a parity checksum.
10. (original) The method of claim 9 wherein the block code is a Hamming(16, 11) code.
11. (withdrawn) The method of claim 1 wherein an encryption parameter is carried in one of the bursts comprising the signaling field, and wherein a receiving device of the plurality of bursts knows a location of the burst carrying the encryption parameter *a priori*.
12. (withdrawn) In a wireless communication system with an air interface comprising a plurality of bursts, a method comprising the steps of:
  - receiving a burst comprising a field embedded within the burst;
  - determining whether the field is one of a synchronization field and a signaling field; and
  - when the field is determined to be the synchronization field, identifying a position of at least one subsequent burst comprising the signaling field, and identifying at least one subsequent burst comprising the synchronization field.

Appl. No. 10/799,813  
Amdt. Dated October 26, 2005  
Reply to Office Action of October 19, 2005

Docket No. CM06187H  
Customer No. 22917

13. (previously presented) In a wireless communication system with an air interface comprising a plurality of bursts, a method comprising the steps of:
- receiving a burst comprising payload and a field embedded within the burst;
  - determining whether the field is one of a synchronization field and a signaling field wherein the synchronization field comprises a synchronization pattern; and
  - when the field is determined to be the synchronization field, identifying a position of at least one subsequent burst comprising the signaling field, and identifying at least one subsequent burst comprising the synchronization field;
  - comparing the received synchronization pattern against a first known synchronization pattern and a second known synchronization pattern;
  - if the received synchronization pattern is substantially similar to the first known synchronization pattern, processing the payload as voice; and
  - if the received synchronization pattern is substantially similar to the second known synchronization pattern, processing the payload as non-voice.
14. (original) The method of claim 13 wherein the first known synchronization pattern and the second known synchronization pattern are complements of each other.
15. (currently amended) The method of claim 13 further comprising the steps of:
- receiving a burst comprising payload and a synchronization field, wherein the synchronization field comprises a synchronization pattern;
  - selecting a target synchronization pattern dependent on an operating mode, wherein the target synchronization pattern is at least one of the first known synchronization pattern and the second known synchronization pattern;
  - comparing the received synchronization pattern against the target synchronization pattern; and
  - if the received synchronization pattern is substantially similar to the target synchronization pattern, processing the payload; otherwise, discarding the burst.

Appl. No. 10/799,913  
Amdt. Dated October 26, 2005  
Reply to Office Action of October 19, 2005

Docket No. CM06187H  
Customer No. 22917

16. (original) The method of claim 15 wherein the operating mode is the expectation of one of an inbound channel, outbound channel, forward channel, reverse channel, subscriber transmission, base station transmission, repeated transmission, and non-repeated transmission.

17. (currently amended) ~~The method of claim 13 further comprising the steps of:~~ In a wireless communication system with an air interface comprising a plurality of bursts, a method comprising the steps of:  
receiving a burst comprising payload and a field embedded within the burst;  
determining whether the field is one of a synchronization field and a signaling field  
wherein the synchronization field comprises a synchronization pattern; and  
when the field is determined to be the synchronization field, identifying a position of at least one subsequent burst comprising the signaling field, and identifying at least one subsequent burst comprising the synchronization field;  
~~receiving a synchronization field, wherein the synchronization field comprises a synchronization pattern;~~  
comparing the received synchronization pattern against a first known synchronization pattern and a second known synchronization pattern, wherein the first and second known synchronization patterns have a common length;  
if the received synchronization pattern is substantially similar to the first known synchronization pattern, selecting a first operating mode; and  
if the received synchronization pattern is substantially similar to the second known synchronization pattern, selecting a second operating mode.

18. (original) The method of claim 17 wherein the first known synchronization pattern is defined by a synchronization pattern defined in ANSI.102.BAAA.

19. (previously presented) The method of claim 13 wherein at least one burst comprising the signaling field carries link control signaling and framing information for the link control signaling.

Appl. No. 10/799,913  
Amdt. Dated October 26, 2005  
Reply to Office Action of October 19, 2005

Docket No. CM06187H  
Customer No. 22917

20. (original) The method of claim 19 wherein an encryption parameter is carried in one of the bursts comprising the signaling field, and wherein a receiving device of the plurality of bursts knows a location of the burst carrying the encryption parameter *a priori*.

21. (previously presented) The method of claim 13 wherein an encryption parameter is carried in one of the bursts comprising the signaling field, and wherein a receiving device of the plurality of bursts knows a location of the burst carrying the encryption parameter *a priori*.

22. (currently amended) The method of claim 13 further comprising the steps of:  
when a burst comprising the ~~signaling~~synchronization field is expected to be received, comparing a pattern in the ~~signaling~~synchronization field against a known synchronization pattern, and

if the pattern in the ~~signaling~~synchronization field is substantially similar to the known synchronization pattern, setting at least one of a set of operating parameters and an operating mode based on the known synchronization pattern.

23. (currently amended) The method of claim 1 wherein if the field is a signaling field and the indicator of the signaling field is not one taken from the group of a) begins a new packet, b) completes a packet, and c) signals a segment of a packet that neither begins nor completes the packet~~does not begin or complete a packet then it identifies a second type of information.~~

Appl. No. 10/789,913  
Amdt. Dated October 26, 2005  
Reply to Office Action of October 19, 2005

Docket No. CM06187H  
Customer No. 22917

24. (currently amended) In a wireless communication system with an air interface comprising a plurality of bursts, a method comprising the step of defining a plurality of bursts, wherein each burst comprises a field embedded within the burst; and wherein the field is one taken from the group of a synchronization field and a signaling field; and wherein, when the field is a synchronization field, defining a position of at least one subsequent burst comprising the signaling field, and defining a position of at least one subsequent burst comprising the synchronization field; wherein, when the field is a signaling field, defining an indicator to identify that payload in the burst either a) begins a new packet, completes a packet, or does not begin or complete a packet or b) identifies a second type of information; and wherein at least one burst comprising the signaling field carries a) link control signaling or a second type of information and b) framing information for the link control signaling or the second type of information.